

Maintenance instructions



LAUTEX metal ceilings are easy cleanable and almost maintenance-free. They are manufactured using 0,4 – 0,7 mm aluminium or steel (coil or sheet), depending of the product type. The durable and anticorrosive surface finish is obtained by using polyester paint or by anodising of aluminium (alternatively galvanised steel). All LAUTEX surface types are very resistant and durable.

For removal of possible stains, the ceiling surface can be cleaned by using a soft cotton cloth moistened with mild soap based detergent or neutral household cleaner (ph 7). Wipe off by using a dry soft cloth. To remove grease, use a purified alcohol based product.

For dust removal use soft brush or vacuum cleaner with soft-brushed head.

Ceilings with mirror finishing or with other delicate surfaces please use cotton gloves when handling in order to prevent visible grease stains or finger marks.

Even though the LAUTEX ceilings are very durable, never use grinding or polishing or other strong detergents or sharp tools for cleaning.

To access the technical spaces behind the ceiling construction, and in cases where there are no service hatches or any easily removable panels available, then the dismantling of the ceilings should be carried out by professional installation company or strictly according to LAUTEX installation instructions, which vary according to the specific ceilings.

Attention: Use dry cleaning only when cleaning perforated ceilings with acoustic felt inlay (the acoustic felt may be get damaged by moisture or water)

If you have any questions, please contact our [technical sales support](#)